



**TRASH CHUTE SPECIFICATIONS:**

- 16 GAUGE ALUMINIZED STEEL CONSTRUCTED CHUTE WITH STANDARD 10" CHUTE THROAT TO ACCOMMODATE THE DOOR.
- INTAKE SECTION(S) AS PER SPECIFICATIONS DENOTING DOOR SIZE.
- ANGLE IRON FLOOR FRAMES TO SUPPORT CHUTE FROM EACH FLOOR LEVEL.
- 165° F. SPRINKLERS TO BE INSTALLED AT THE TOP INTAKE AND INSTALLED AT EVERY ALTERNATE INTAKE BELOW. SPRINKLERS ARE READY FOR PIPING BY OTHERS.
- CHUTE TO EXTEND MINIMUM 3' (PER NFPA) ABOVE ROOF OR BULKHEAD WITH AN EXPLOSION RELEASE ROOF VENT.
- ROLLING DISCHARGE GATE IS HIGHLY RECOMMENDED FOR TRASH CHUTE INSTALLATIONS. THE DOOR IS OF "B" LABEL CONSTRUCTION AND IS EQUIPPED WITH A FUSIBLE LINK DESIGNED TO CLOSE IN CASE OF FIRE.
- HOPPER TYPE DISCHARGE ASSEMBLY IS HIGHLY RECOMMENDED FOR LINEN CHUTE INSTALLATIONS. THE DOOR IS SELF CLOSING TOP HINGED, UL "B" STAINLESS STEEL DOOR HELD IN PLACE WITH A UL APPROVED 165° F FUSIBLE LINK.
- ACCESSORY ITEMS AVAILABLE TO ORDER:
  - A. AUTO-CAD DESIGN SERVICE
  - B. SANITIZER UNIT
  - C. ACCESS DOORS
  - D. SOUND COATING
  - E. ANGLE FRAME ISOLATOR PADS
- SHOP DRAWINGS AND SUBMITTALS DETAIL CHUTE DRAWINGS INDICATING DIMENSIONS, COMPONENTS, ACCESSORIES AND ALL DETAILED INFORMATION IS AVAILABLE UPON REQUEST. THESE SUBMITTALS WILL BE PRODUCED IN AUTO-CAD AND CONVERTED TO PDF FORMAT IF REQUESTED.



53-16 35<sup>th</sup> Street, Suite 3B  
 Long Island City, NY 11101  
 phone: 718-472-5700  
 fax: 718-472-5813  
 web: <http://www.allcitymetal.net>  
 e-mail: [allcitymetal@aol.com](mailto:allcitymetal@aol.com)

**ALL-CITY METAL**  
 SHEET METAL FABRICATORS

**CHUTE DETAIL**