



TRASH CHUTE INTAKE
N.T.S.

TRASH CHUTE INTAKE SPECIFICATIONS:

ALL DOORS HAVE A CLASS B 'UL' RATING WITH A 1-1/2 HOUR FIRE RATING WITH A 30-MINUTE TEMPERATURE RISE OF 250 DEGREES FAHRENHEIT. STANDARD 15"X18" BOTTOM HINGED DOOR ACCOMPANIES TRASH CHUTES. A STANDARD 18"X18" SIDE HINGED DOOR ACCOMPANIES LINEN CHUTES. ALL DOORS ARE FABRICATED WITH TYPE 304 STAINLESS STEEL, STAINLESS STEEL HINGES, WITH A SELF CLOSING, SELF LATCHING QUITE DOOR CLOSING FUNCTION. THE DOOR PANELS ARE COMPLETELY FABRICATED FROM TYPE 304 SATIN FINISH STAINLESS STEEL EQUIPPED WITH A "T" TYPE LEVER LOCKING HANDLE. OUR STANDARD STAINLESS STEEL FRAME IS 1-1/2" WIDE OR CAN BE FABRICATED LARGER TO ACCOMMODATE AN EASY DOOR REPLACEMENT. DOOR TRIM IS EMBOSSED TO INDICATE CHUTE TYPE.



53-16 35th Street, Suite 3B
Long Island City, NY 11101
phone: 718-472-5700
fax: 718-472-5813
web: <http://www.allcitymetal.net>
e-mail: allcitymetal@aol.com

ALL-CITY METAL
SHEET METAL FABRICATORS

TRASH CHUTE INTAKE