

APARTMENT COMPACTOR MC3000-MINI

GENERAL DESCRIPTION:

Chute-fed, fully automatic, hydraulically operated piston extrusion type horizontal refuse compactor is operated by a single cylinder. Compacted refuse can be extruded into a individual plastic bags or reusable 2 cubic yard containers.



MECHANICAL FEATURES:

- Factory assembled
- Wired and tested prior to shipment
- Chassis (Body) - $\frac{3}{8}$ " thick
- Chassis Impact Plate - $\frac{1}{2}$ " thick
- Ram Housing - $\frac{3}{8}$ " thick
- Ram face plate - 1" thick
- Hopper - 11 Gauge with $\frac{3}{16}$ " thick impact plate

SAFETY FEATURES:

- LED Photoelectric sensor indicating full container
- Compaction ram starts in fully retracted position
- Emergency stop button
- Bag switch chained to tubing disengages compactor when tubing full
- Hopper door switch shuts compactor down when opened
- Manual shut-off gate
- Ram retract button
- 5 Amp fused circuit
- Adjustable overload relay
- Optional sprinkler solenoid assembly (Requires 110v circuit)
- Optional full bag light with audible alarm

	MC3000-MINI
WEIGHT	1,200 LBS
OVERALL DIMENSIONS (W x L x H)	29 $\frac{1}{2}$ " X 61 $\frac{1}{4}$ " X 62 $\frac{1}{2}$ "
CYCLE TIME	13s-14s
RAM FORCE	30,000 LBS @ 2400 PSI
HYDRAULIC CYLINDER	3.5"Ø BORE, 3.14" ROD/ 2.75"Ø BORE, 2.36" ROD & 28" STROKE
CAPACITY	1200 LBS/HOUR
ELECTRIC MOTOR	5 HP, 1,750 RPM, 208/220/440 VOLTS*, 14.7 AMPS, 3 PHASE, 60 CYCLES
BUILDING UNITS	UP TO 50 UNITS



54-35 46TH STREET
MASPETH, NY 11378
(718) 472-5700

EMAIL: info@allcitymetal.com

WEBSITE: www.allcitymetal.com